

**DUBUQUE COUNTY HIGHWAY DEPARTMENT
ANNUAL OVERSIZE PERMIT
(VALID FOR ONE POWER UNIT ONLY)**

Issued by: Dubuque County Engineer's Office
13047 City View Drive
Dubuque, IA 52002
563-557-7283 Fax 563-557-1973

Permit No. _____

Fee: \$25.00

Name				Date		Fax Number	
Address						Check/Cash/Charge	
Power Unit Year & Make		Power Unit License No. & State		Power Unit Registered Weight		Trailer Make	Trailer License No. & State
Interstate Travel Authority Number				Intrastate Travel Authority			US DOT Number
Object or Load		Model Number		VIN		Serial Number	SME Qualified
Overall Length	Width	Height	Total Weight	Trailer Length	Load Length	Projections Front	Rear
Axle Weights		Single 20,000		Tandem 40,000		Triple 60,000	Quad
Axle Spacing							

GENERAL REQUIREMENTS:

Civilian front escort with mounted height pole required entire route if height exceeds 14' 4"

See General Provisions for escort requirements for overwidth vehicles.

Overdimensional signs and flags must be displayed on all overdimensional loads over 75' long or over 8' 6" wide or over 14' 4" high.

Trip routes must be provided to the Engineer's Office for all movements.

No movement allowed on Y50 (Herber), C7Y (Riverside), C9Y (Sherrill), C63 (Ridge), Y34 and Y14 (Kennedy), D12 (Rupp Hollow), John Deere or Peru Roads on weekdays from 6:00am to 9:00am and 3:00pm to 6:00pm.

75' long x 12' 5" wide x 13' 6" high - maximum dimensions for hauling hay.

Speed limit: maximum posted limits unless otherwise specified on permit.

Must carry copy of permit and General Provisions dated 10/01 and comply with them.

Road must be clear of ice and snow and visibility must be at least 1/4 mile.

Necessary state and/or city permits must be obtained separately.

Speed shall not exceed 45 mph on secondary road system.

Speed for mobile homes shall not exceed 40 mph on secondary road system.

Vertical clearances are not guaranteed.

Special Requirement:

Valid Dates:

From _____ through _____ 1/2 hour before sunrise to 1/2 hour after sunset unless qualified for continuous movement.

No movement allowed on Memorial Day, Independence Day and Labor Day per General Provisions.

Signature of Applicant		Phone		Permit Officer	

IOWA GENERAL PROVISIONS FOR OVERSIZE LOAD PERMIT

The State of Iowa, the Iowa Department of Transportation and any other permit issuing authority assume no responsibility for the property of the permit holder. During movement under permit, the permit holder must meet the terms and conditions of the permit and must take all reasonable precautions to protect and safeguard the lives and property of the traveling public and adjacent property owners. A copy of a current certificate of public liability insurance in the amounts of \$100,000 bodily injury each person, \$200,000 bodily injury each occurrence, and \$50,000 property damage must be carried in the vehicle for which the permit has been issued. Nothing shall exempt the permit holder from compliance with any load limitations which have been or might be established on any bridge or road that is posted with embargo signs. The permit and any revisions will be void if the actual weights or dimensions exceed what is indicated on the permit or its revisions. Permits can be issued only for loads that are a single article that cannot be reasonably broken down to make it legal in size and weight. The permit must be carried in the cab of the vehicle for which it has been issued and be available for inspection.

Movement is allowed seven days a week except for designated holidays and for special events when abnormally high traffic counts can be expected. The designated holidays are: Memorial Day, Independence Day and Labor Day. No movement will be allowed on these holidays or after 12 noon on days preceding these holidays and holiday weekends which include holidays that fall on Monday, except as provided for in Section 321.457 of the Code.

Any reportable accident involving a vehicle operating under permit must be reported in writing to the Director of the Office of Motor Carrier Services, Park Fair Mall, 100 Euclid Avenue, P.O. Box 10382, Des Moines, IA 50306-0382.

Escort Requirements - Escorts must be at least 18 years old, possess a valid Class A, B, C or D driver's license, and carry proof of public liability insurance in the amounts of \$100,000/\$200,000/\$50,000. The escort vehicle must be approximately the size of a normal passenger automobile or pickup and must have an amber revolving light. The light must be at least 7" high and 7" in diameter, with at least a 100-candlepower lamp providing 360° warning (or a strobe light), and be mounted on top of the escort vehicle which must be burning while escorting a permit load. An 18" square red flag must be on each corner of the front bumper of the vehicle.

- A rear escort is required when vehicle length exceeds 120 feet.
- A rear escort is required when the width of the vehicle and load is over 16' 6" and travel is on 4 lane roadways.
- A rear escort or an amber light or strobe light on the power unit and on the rear extremity of the vehicle or load when width exceeds one-half the roadway up to and including 16' 6" and travel is on 4 lane roadways.
- A front escort is required when: Width is up to and including 14' 6" and exceeds one-half the roadway and travel is on 2 lane roadways with lane width less than 12' OR width is up to and including 14' 6" and exceeds one-half the roadway and travel is on 2 lane roadways with lane width 12' or more without sufficient shoulders OR width is over 14' 6" and travel is on 2 lane roadways.
- A front escort - or amber light or strobe light on the power unit and on the rear extremity of the vehicle or load, when width is up to and including 14' 6" and exceeds one-half the roadway and travel is on 2 lane roadways with lane width 12' or more with sufficient shoulders.
- A front escort with mounted height pole is required when height exceeds 14' 4" up to and including 20'. An escort but no height pole is required after 20'.

Lighting Requirements - An amber revolving light at least 7" high and 7" in diameter with at least a 100-candlepower lamp providing 360° warning (or strobe light) visible from front and rear, mounted on the towing unit is required when: Length exceeds 85' up to and including 120' OR Front-end projection exceeds 25' OR Rear-end projections exceeds 10' OR weight exceeds 80,000 pounds. An escort can be used in lieu of amber light.

Signs and Flags - Signs and flags are required when a vehicle and load exceeds 75' in length, 8' 6" in width, and/or 14' 4" in height. In addition, flags are required when the vehicle rear projection exceeds 4'. A sign reading "Oversize Load" must be at least 18" high by 7' long with a minimum of 12" black letters with a 1-1/2" stroke, on a yellow background, and mounted on the front bumper and on the rear of the load. A rear sign for mobile homes must be mounted at least 7' above the highway surface, measuring from the bottom of the sign. Flags must be red or orange fluorescent and at least 18" square must be mounted as follows: one flag at each front corner of the towing unit and one flag at each rear corner of the load. In addition, there must be a flag at any additional protrusion in the width of the load. The signs or warning devices must be mounted so they can be removed or covered when the vehicle is within legal dimensions.

Definition of sufficient shoulder - A gravel or paved surface extending a minimum of 6' beyond the edge of the roadway.

Requirements for Continuous Moves - Vehicles and loads may travel by permit between 1/2 hour after sunset and 1/2 hour before sunrise if, in addition to the general provisions and general requirements specified by the permit, the following conditions are met.

A. Dimensions shall not exceed:

1. Width 11 feet
2. Height 14feet, 4 inches
3. Length 100 feet
4. Weight Permitted axle limits

B. Travel must be on roadways with a minimum width of 22 feet and minimum lane width of 11 feet.

C. Safety lighting shall be provided at the widest part of the load. The lamps may be placed at the outer ends of the load itself or on appurtenances which are equal in width to the widest part of the load and positioned at both extreme front and rear of the vehicle or trailer as follows:

1. One lighted red lamp on each side at the rear of the load
2. One lighted yellow or amber lamp on each side at the front of the load.

Telephone number for more information (515) 237-3264